



REPLACEMENT PARTS LIST

ITEM	PART NO.	DESCRIPTION	QTY.
1	054133	ASSEMBLY: SHEAVE	1
2	053513	ASSEMBLY: CABLE (40" LIFT CABLE)	1
3	151294	WINCH COMPLETE (3 MOUNTING HOLES)	1
	108504	WINCH COMPLETE (2 MOUNTING HOLES PRE-1996)	1
4	108501	ROLLER: PLATFORM CAM	4
5	151294	KIT: WHEEL LOCK "FOOT STYLE" (STL PL-40/54)	1
		KIT: WHEEL LOCK "HANDLE STYLE" (PL-40)	1
6	052868	WHEEL: "H1" 8 X 2	2
7	051813	KIT: PLATFORM ROLLER W/ HARDWARE	4

STEEL FRAME PEDALIFTS

- Wheel locks are standard on all models.
- Frame and lift heights vary among models.
- Adjustable fork widths outer dimensions are 6-1/2" to 21-7/8" wide

Two Wheeled Winch Models Features:

- Auto-brake designed winch raises and lowers by turning handle, no catches to lock or release required.
- Low maintenance design.
- Front of platform touches the ground on two wheeled model.
- Wheel lock standard.

P/N 260018  
 Model: WPL-40-F  
 Lift Height: 40"  
 Fork: 18"D X 3"W  
 Weight: 125 lb.  
 Capacity: 750 lb.  
 O.A.H 48.5" High  
 O.A.W 22.5" Wide

THIS DRAWING IN ALL PARTICULARS IS WESCO MFG. CO. PROPERTY. ALL RIGHTS OF DESIGN, INVENTION OR USE OF ARE RESERVED.

PRINT ISSUED  
 NOV 12, 2004  
 WESCO MANUFACTURING  
 ENGINEERING DEPARTMENT

REV. ECH & DATE	APP	WESCO MANUFACTURING CO. NORTH WALES PENNA. 19454	
	REVISIONS	PART NAME WPL-40-F (FRAME: 053138)	DRAWN:
		TOLERANCE UNLESS OTHERWISE SPECIFIED	CHECKED:
		FRACTION 3 PLACE DECIMAL 2 PLACE DECIMAL	APP. ENGR.
		± 1/64 ± .005 ± .01	SCALE:
	ANGULAR ± 1-1/2°	SHEET 1 OF 1	C-260018 REV
		BREAK ALL SHARP EDGES AND REMOVE ALL BURRS	