



Foot and Powered Portable Hydraulic Lift Table

- AC and DC power option available.
- 0.25" reinforced steel top and base.
- 2 rigid and 2 swivel steel wheel casters.
- Standard designs available in 2 sizes: 30" x 30" and 48" x 30"
- Available in 4 capacities: 3,000 4,000 5,000 and 6,000.
- Precision telescoping guide tubes.

Specs

- Capacity: 6000 lbs
- Table size: 30" x 30"
- Raised height: 54"
- Lowered height: 31"
- Caster: 6"
- Lift: 23"
- Weight(foot opp.): 480 lbs
- Weight(electric opp.): 531 lbs

THIS DRAWING IN ALL PARTICULARS IS WESCO INDUSTRIAL PRODUCTS INC. PROPERTY. ALL RIGHTS OF DESIGN, INVENTION OR USE OF ARE RESERVED.

REV.	ECN & DATE	REVISIONS	WESCO INDUSTRIAL PRODUCTS INC.							
			LANSDALE PENNA. 19446							
			PART NAME HT-3036-23		DRAWN:					
			TOLERANCE UNLESS OTHERWISE SPECIFIED		CHECKED:					
			FRACTION 3 PLACE DECIMAL 2 PLACE DECIMAL		APP. ENGR.					
			<table border="1" style="width: 100%;"> <tr> <td style="width: 50%; text-align: center;">± 1/64 ± .005 ± .01</td> <td style="width: 50%; text-align: center;">ANGULAR ± 1-1/2'</td> </tr> <tr> <td colspan="2" style="text-align: center;">SHEET 1 OF 1</td> </tr> <tr> <td colspan="2" style="text-align: center;">BREAK ALL SHARP EDGES AND REMOVE ALL BURRS</td> </tr> </table>		± 1/64 ± .005 ± .01	ANGULAR ± 1-1/2'	SHEET 1 OF 1		BREAK ALL SHARP EDGES AND REMOVE ALL BURRS	
± 1/64 ± .005 ± .01	ANGULAR ± 1-1/2'									
SHEET 1 OF 1										
BREAK ALL SHARP EDGES AND REMOVE ALL BURRS										
			B- 496057	REV						